

Q39-12



MICROIMPULSE TECHNOLOGY
ONBOARD



SCRUBBER DRYER LINE

WWW.RRINTERNATIONAL.IT

TECHNICAL FEATURES



39-12

MACHINE

Rectangular plate with micro-impulse movement (exclusive in the sector), 2 brush motor power levels Eco-Max and Eco-Mode, simple adjustment of the water flow rate with tap, solution drain facilitated by display, easily accessible solution filter, level sensor dirty water stop-total in the recovery tank, optical solution level indicator, instant water shut-off button.

SUCTION SYSTEM

Powerful and silent, independent single-stage turbine, 3 levels of suction power, standard air filter to protect the turbine, standard H13 Hepa filter on the turbine exhaust.

INNOVATION ON BOARD

3 ON/OFF switches: brushes (2 speeds) – turbine (3 speeds) and solution delivery (on/off) innovative and practical display, hour counter, charge status with % remaining lithium battery, yield counter with display indicating sq. m. progressive and daily cleaning, and the average m²/h, absorbed power indicator (W).

COMFORT

Light and easy to transport in a car or van, short and compact for easy handling in small spaces. Large 200mm rear wheels in non-marking and anti-skid rubber for easy transport. Ergonomic control handle with foldable handle for easy transport. Tank in tank : recovery tank with large compartment and easy to clean



Voltage	54,6V
Potenza totale installata	450 W
Tank capacity	12 Lt
Recovery tank capacity	14 Lt.
Productivity	1.600 m ² /h
NOISE LEVEL	66,7 dB(A)
Length	750 mm
Width with squeegee	490 mm
Height	1.100 mm
Protection rate	IPX3
Working width	Cm 39 x cm 23
Brushes rpm	2800
Load on brushhead	Kg.23
Water Flow	1 Lt min
Battery capacity	7.8A Li-Ion con BMS
Battery Runtime	1 H
Charger	3A UL certified
Charging time	2h
Total weight unit	35 Kg
Packaging size	750x530x820 mm
Weight with packaging	45 Kg



RR INTERNATIONAL SRL

Via Le Lamie N°9

70015- Noci (BA) Italy

Mail: info@rrinternational.it

WWW.RRINTERNATIONAL.IT

